




System Hardware Setup

1. Connect Topside Modem to Topside Battery Unit with provided cable.
2. Connect Topside Battery Unit to USB port on the Diver6 Tablet with provided cable.
3. Turn on Battery Unit & Computer.



Start Diver6 Software

1. Click P1 on the computer or click the Diver6 Icon in Start or the taskbar.
2. Click Agree to use the system.
3. Login your Dive Master account or create one using the **Manage Dive Masters** button.



Verify and Setup Topside & GPS Communication Ports


1. Click “Configuration” from the Main Menu and then “Communication.”
2. Click the appropriate device button on the left side of the screen. Then, click the “Rescan Ports” to collect all available Comm ports.
3. Select a Comm port. Click the “Test Connection.”
4. If you get a “Success” you have the proper port. If you get a “Fail” select a different port and retest. If no port gives you a “Success” message, check all your hardware connections.
5. Repeat Step 2 for each available device (Topside Modem, GPS, Compass).

Bluetooth

When using Bluetooth, be sure that the module is plugged into the computer and the LED is solid. A flashing LED means the unit is attempting to connect.

GPS Comm Port Settings


Baud Rate: 4800
Data Bits: 8
Parity: None
Stop Bits: 1
Flow Control: Off



Manage Divers


1. Start Diver 6 Software & Login.
2. Click “Manage Divers” from the Main Menu.
3. Click the “Create Diver” button to create a new diver. Enter the diver information and click “OK.”
4. Edit an existing diver by clicking on an existing diver profile and then clicking “Edit Diver.” Update the information and click “OK.”
5. Edit Diver Alarms by clicking an existing diver profile and then clicking “Edit Diver Alarms.” Update the information and click “OK.”
6. Delete a diver by clicking the diver profile you wish to delete. Click the “Delete Diver” button and follow the steps.

Note: Be sure that the diver is configured with the proper modem ID for the Diver Modem being used.



Executing the Dive

1. Click the “Dive Plan” button from the Main Menu.
2. Fill in the appropriate information for the dive at the top.
3. Select the diver from the “Available Divers” list. Place diver in the “Active Divers” list box.
4. Click the “Monitor Dive” button when all the divers are added.
5. Make sure all divers are verified as “On Surface” by the software. Check the Dive Team Control settings to verify if necessary.
6. Click the “Complete Dive” button.



Diagnostics

If you are having issues communicating with equipment use Diagnostics.

Note: When checking Diver modems only one modem can be on at a time.

1. Complete the System Hardware Setup on this Quick Start Guide.
2. Login to Diver6 Software.
3. Click “Diagnostics” from the Main Menu.
4. Check each piece of your system by following the directions on screen.

Note: If a dive is running (active) diagnostic testing is disabled.

